


PROFESSIONAL  
LIGHTING  
FOR THE  
PERFORMING ARTS

Product catalogue 2022






## Fresnel



Luminaires with fresnel lens, adjustable yoke and optical zoom.  
Recommended for soft and even lighting.  
Available with motorized yokes with DMX control or pole operated yokes.



	<b>FN LED 50</b>	<b>FN LED 50 RGBW</b> 
Power	50W	50W
LED	White (3000K, 4000K, 5600K)	RGBW
Control	- DMX-RDM - Local	- DMX-RDM - Local
Version	12°-76° (2,5kg - 27x16x25cm)	13°-50°



	<b>FN LED C100</b>
Power	100W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	12°-75° (3,5kg - 29x22x31cm)

	<b>FN HY LED 200</b>	<b>FN HY LED 200 Tunable</b> 	<b>FN HY LED 200 RGBW</b> 	<b>FN HY LED 200 6C</b> 
Power	200W	200W	200W	200W
LED	White (3000K, 4000K, 5600K)	White (2700K-6500K)	RGBW	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Versions	14°-81°	13°-50°	13°-50°	13°-50°

	<b>FN HY LED 300</b>	<b>FN HY LED 300 Tunable</b> 	<b>FN HY LED 300 6C</b> 
Power	300W	300W	300W
LED	White (3200K, 5600K)	White (2700K-6500K)	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Version	09°-45°	09°-45°	12°-45°

	<b>FN HY LED 700</b>	<b>FN HY LED 700 Tunable</b> 	<b>FN HY LED 700 8C (6C + Tunable)</b> 
Power	700W	700W	700W
LED	White (3200K, 5600K)	White (2700K-6500K)	RGB+AMBER+CYAN+LIME+WW+CW
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Version	11°-53°	11°-53°	11°-53°

	<b>MI FN NO</b>	<b>COM 05 F</b>	<b>COM 12 F</b>	<b>COM 25 F</b>
Source	Halogen	Halogen	Halogen	Halogen
Power	300W (GY 9,5)	500/650W (GY 9,5)	1000/1200W (GX 9,5)	2000/2500W (G 22)
Version	07°-53° (1,3kg - 11x13x17cm)	07°-62° (3kg - 15x15x25cm)	07°-53° (5,4kg - 20x20x30cm)	07°-65° (10,8kg - 27x29x41cm)

## Plano-Convex

Luminaires with prism-convex lens, adjustable yoke and optical zoom.  
Recommended for soft and accent lighting.  
Available with motorized yokes with DMX control or pole operated yokes.

### PC LED 50

Power	50W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	08°-80° (3kg - 27x16x29cm)

### PC LED C100

Power	100W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	15°-75° (3,5kg - 29x22x31cm)



### PC HY LED 200

Power	200W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	16°-87°

### PC HY LED 200 Tunable

Power	200W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	15°-50°

### PC HY LED 200 RGBW

Power	200W
LED	RGBW
Control	- DMX-RDM - Local
Version	15°-50°

### PC HY LED 200 6C

Power	200W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	15°-50°

### PC HY LED 300

Power	300W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	06°-45°

### PC HY LED 300 Tunable

Power	300W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	06°-45°

### PC HY LED 300 6C

Power	300W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	08°-45°

### PC HY LED 700

Power	700W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	13°-54°

### PC HY LED 700 Tunable

Power	700W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	13°-54°

### PC HY LED 700 8C (6C + Tunable)

Power	700W
LED	RGB+AMBER+CYAN+LIME+WW+CW
Control	- DMX-RDM - Local
Version	13°-54°

### MI PC NO

Source	Halogen
Power	300W (GY 9,5)
Version	07°-53° (1,6kg - 11x13x22cm)

### COM 05 PC

Source	Halogen
Power	500/650W (GY 9,5)
Version	04°-56° (3,7kg - 15x15x30cm)

### COM 12 PC


Source	Halogen
Power	1000/1200W (GX 9,5)
Version	04°-63° (6,8kg - 20x20x40cm)

### COM 25 PC

Source	Halogen
Power	2000/2500W (G 22)
Version	04°-66° (13,7kg - 27x29x53cm)




## Profile



Luminaires with adjustable shutters, yoke, optical zoom and focus.  
Recommended for accent and precise lighting, as well as for images projection (gobos).  
Available with motorized yokes with DMX control or pole operated yokes.



	PR LED 50	PR LED 50 RGBW 
Power	50W	50W
LED	White (3000K, 4000K, 5600K)	RGBW
Control	- DMX-RDM - Local	- DMX-RDM - Local
Version	20°-40° (4,1kg - 37x37x43cm)	20°-40°

	PR LED 100
Power	100W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Versions	20°-38° (6kg - 40x34x54cm) 35°-50° (6kg - 40x34x45cm)



	PR HY LED 200	PR HY LED 200 Tunable 	PR HY LED 200 RGBW 	PR HY LED 200 6C 
Power	200W	200W	200W	200W
LED	White (3000K, 4000K, 5600K)	White (2700K-6500K)	RGBW	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Versions	15°-30° 25°-50°	15°-30° 25°-50°	15°-30° 25°-50°	15°-30° 25°-50°

	PR HY LED 300	PR HY LED 300 Tunable 	PR HY LED 300 6C 
Power	300W	300W	300W
LED	White (3200K, 5600K)	White (2700K-6500K)	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Versions	15°-30° 25°-50°	15°-30° 25°-50°	15°-30° 25°-50°

	PR HY LED 700	PR HY LED 700 Tunable 	PR HY LED 700 8C (6C + Tunable) 
Power	700W	700W	700W
LED	White (3200K, 5600K)	White (2700K-6500K)	RGB+AMBER+CYAN+LIME+WW+CW
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Versions	08°-25° 20°-40°	08°-25° 20°-40°	08°-25° 20°-40°

	MI PR ZS NO	COM 05 ZS/ZW	COM 12 ZS/ZM	COM 25 ZS/ZW
Source	Halogen	Halogen	Halogen	Halogen
Power	300W (GY 9,5)	500/650W (GY 9,5)	1000/1200W (GX 9,5)	2000/2500W (G 22)
Versions	20°-40° (1,3kg - 11x13x17cm)	14°-33° (4,8kg - 15x15x49cm) 23°-40° (4,5kg - 15x15x40cm)	13°-35° (9,8kg - 20x20x72cm) 24°-50° (9,1kg - 20x20x57cm)	09°-25° (25,1kg - 27x29x90cm) 17°-36° (21,3kg - 27x29x79cm)

## Followspot

Luminaires with adjustable shutters, yoke, optical zoom and focus. Built-in manual colour changer included in LED versions.

Recommended for accent and long distance lighting, with direct control from the operator.



### FS HY LED 300

Power	300W
LED	White (5600K)
Control	- DMX-RDM - Local
Version	07°-14°

### FS HY LED 700

Power	700W
LED	White (5600K)
Control	- DMX-RDM - Local
Version	07°-14°



### VD 12 M CR

Source	Discharge
Power	1200W / MSR (GY 22)
Standard	Cold Restrike version, Iris diaphragm with black out, shaping shutters and slots for B size gobo holder
Distance	20-40 m
Version	07°-18° (18,8kg - 20x20x112cm)

### VD 12 M HR

Source	Discharge
Power	1200W / MSR (G 38)
Standard	Hot Restrike version, Iris diaphragm with black out, shaping shutters and slots for B size gobo holder
Distance	20-40 m
Version	05°-13° (18,8kg - 20x20x112cm)

### VD 25 H

Source	Halogen
Power	2000/2500W (G 22)
Standard	Iris diaphragm with black out, shaping shutters and slots for A size gobo holder
Distance	15-25 m
Version	07°-16° (27kg - 27x29x115cm)

### VD 25 M HR

Source	Discharge
Power	2500W / MSR (G 38)
Standard	Hot Restrike version, Iris diaphragm with black out, shaping shutters and slots for B size gobo holder
Distance	30-100 m
Version	05°-13° (51kg - 27x29x163cm)



## Floodlight

### Asymmetric

For the illumination of large areas and cycloramas. Suitable both for lighting from the floor and from the top.

#### DOM 1000

Source	Halogen
Power	1000/1250W (R7s)
Version	3,8kg - 29x28x21cm





### Asymmetric

Asymmetric cyclorama powered by LED source in RGBW. Thanks to its sophisticated specifically designed optical system, it allows to illuminate in an absolutely even way an area of over 40 sqm when positioned at a distance from the backdrop of only 1,5m.

#### CYC LED 300 RGBW

300W
RGBW
- DMX-RDM
- Local
15kg



Professional lighting for the performing arts since 1969

## Downlight

Recessed LED luminaires with high-efficiency white chip. High quality polycarbonated aluminate optics.

	<b>HAL LED 55</b>	<b>HAL LED 90</b>
Power	50W (no fan)	90W (no fan)
LED	White (3000K, 4000K, 5600K)	White (3000K, 4000K, 5600K)
Control	- DALI	- DMX-RDM
	- Local	- Local
	- DMX-RDM (opt.)	
Versions	29° (0,75kg - 16x16x14cm)	29° (0,75kg - 16x16x14cm)
	46° (0,75kg - 16x16x14cm)	46° (0,75kg - 16x16x14cm)
	72° (0,75kg - 16x16x14cm)	72° (0,75kg - 16x16x14cm)



Professional lighting for the performing arts since 1969




## Pinspot

Architectural pinspot with integrated LED source.



	<b>MINILUT LED 15</b>	<b>MINILUT LED 30</b>	<b>SUPERLUT LED 30</b>	<b>SUPERLUT</b> (for halo and non-dimmable LED)
Power	15W, 48V, max 60VDC	30W, 48V, max 60VDC	30W, 230V, 230VAC	max 75W, 12V, R-111
LED	White (3000K, other on request)	White (3000K, other on request)	White (3000K, other on request)	Lamp not included
Control	- DALI - Casambi	- DALI - Casambi	- Dimmable from mains	
Versions	15° (0,8kg - 18x16x22cm) 26° (0,8kg - 18x16x22cm)	15° (1,2kg - 18x16x22cm) 26° (1,2kg - 18x16x22cm)	15° (1,5kg - 18x16x22cm) 26° (1,5kg - 18x16x22cm)	(depends on mounted lamp)



Professional lighting for the performing arts since 1969



## Pole Operated system

Pole Operated yokes: modular system of yokes with 2 o 3 functions (tilt, pan and focus) with safet clutch to protect gear box and to allow hand focusing



## ARC system

Automated Remote Control: motorised DMX modular yokes for high precision 16 bit focusing for tilt, pan, beam adjustment. Thanks to the modular structure it accepts all LED and Conventional Spotlight fixtures and most of the luminaires commercially available on the market.



Ed. 04/2022



## Operational Headquarters

Via Sardegna, 3 - 20098 - S. Giuliano Milanese (MI) - Italia

[www.spotlight.it](http://www.spotlight.it)

## Registered Office

Via Martino Anzi 8, 22100 Como (CO) - Italia